



TYPE C PIN(J1)	COLOR/Conductor
A1 A12 B1 B12 SHELL	BLACK(GND)
A4 A9 B4 B9	WHITE(VBUS)
A5	BLUE(CC1)

P/N.:9NA0606006

THIRD ANGLE PROJECTION		DIMENSIONAL TOLERANCES		HOLES : ±0.05	ANGLES : ±0.5°
( )	( ✓ )	( )	( )		
<30 : ±0.2	DECIMALS	UP~100 : ±0.2	250~300 : ±0.4	UP~600 : ±1.5	
>30~100 : ±0.3	X : ±0.8	100~150 : ±0.25	300~350 : ±0.45	600~900 : ±2.4	
>100~200 : ±0.4	XX : ±0.5	150~200 : ±0.3	350~400 : ±0.5	900~OVER : ±3.1	
>200~300 : ±0.5	XXX : ±0.3	200~250 : ±0.35			
ABOVE 300 : ±0.8					

Functional Ground R/C Type:	R = 22K ohm, C = Not Assenbled
Registration Number:	C190329001
Switch from:	X

MODEL NO. : G.P.FSP060-D1AR4(F660002)		TITLE: ASSY		SHEET: 1 OF 1	REV:02
R&D5 Division	P E	DRAWN	DATE		
JERRY	VICTORYU	ANGELH	JUL.30.2019		
INTERIOR COUNTERSIGN:				OAD-00005050	Beth; Stella