



REF. ID.	PIN NO.	SIGNAL	WIRE COLOR	GAUGE	CONNECTOR TYPE	CABLE LENGTH
P1	1	+3.3V	ORANGE	20	WST	400±15mm
	2	+3.3V	ORANGE	20	P20-	
	3	COM	BLACK	20	I42002K11DZ	
	4	+5V	RED	20	-W	
	5	COM	BALCK	20	+P4-	
	6	+5V	RED	20	I42002K11DZ	
	7	COM	BALCK	20	-W	
	8	PW-OK	GRAY	24	or EQUIV.	
	9	PW-OK	GRAY	24		
	10	+5Vsb	PURPLE	24		
	11	+5Vsb	PURPLE	24		
	12	+12V	YELLOW	20		
	13	+12V	YELLOW	20		
	14	+3.3Vsense	BROWN	24		
	15	-12V	BLUE	24		
	16	COM	BALCK	20		
	17	PS-ON	GREEN	24		
	18	PS-ON	GREEN	24		
	19	COM	BALCK	20		
	20	COM	BALCK	20		
	21	+5V	RED	20		
	22	+5V	RED	20		
	23	+5V	RED	20		
	24	COM	BALCK	20		
P2	1	COM	BALCK	20	MOLEX	410±15mm
	2	COM	BALCK	20	39-01-	
	3	+12V	YELLOW	20	2045	
	4	+12V	YELLOW	20	or EQUIV.	
PA	1	+12V	YELLOW	20	WST	250±15mm
	2	COM	BALCK	20	P4-A1020Z	
	3	COM	BALCK	20	or EQUIV.	
	4	+5V	RED	20		
PB	1	+5V	RED	20	AMP	155±10mm
	2	COM	BALCK	20	171822-4	
	3	COM	BALCK	20	or EQUIV.	
	4	+12V	YELLOW	20		
PC	1	+12V	YELLOW	20	WST	310±15mm
	2	COM	BALCK	20	P4-A1020Z	
	3	COM	BALCK	20	or EQUIV.	
	4	+5V	RED	20		
PD	1	+12V	YELLOW	20	WST	155±10mm
	2	COM	BALCK	20	P4-A1020Z	
	3	COM	BALCK	20	or EQUIV.	
	4	+5V	RED	20		
PE	1	+3.3V	ORANGE	20	WST	310±15mm
	2	COM	BALCK	20	P5-I2702T00	
	3	+5V	RED	20	or EQUIV.	
	4	COM	BALCK	20		
	5	+12V	YELLOW	20		
PF	1	+3.3V	ORANGE	20	WST	155±10mm
	2	COM	BALCK	20	P5-11271B	
	3	+5V	RED	20	-B	
	4	COM	BALCK	20	or EQUIV.	
	5	+12V	YELLOW	20		

NOTE:

- ALL THE LENGTH OF OUTPUT WIRES EXCLUDE HOUSING.
- 公差: .XX=±0.5 [0.02]、.XXX=±0.25 [0.01]

UNIT:mm [inch]

MODEL NO. : FSP220-50FGGBI(F660001)		TITLE: ASSY		SHEET: 1 OF 1		REV:01
R&D(2)	PE	DRAWN	DATE			
		周書宇	MAR.30.2018			
INTERIOR COUNTERSIGN:				FPS		

P/N.:9PA2203501